

For Commercial

## PFH-FFC

---

Applicable Water quality: Tap Water

Applicable place: coffee shop, tea shop, restaurant, convenience store


## Product Advantages

Comply with US NSF42 standard

FFC filter uses composite filter material: Japanese silver-loaded carbon fiber rod and high-precision folding membrane

Filtration accuracy up to 0.45 um micron, can inhibit the bacteria

## Product Specifications

				
Model	PFH1-FFC	PFH2-FFC	PFH3-FFC	PFH4-FFC
Flow Rate	1.7GPM / 6.4LPM	3.4GPM / 12.9LPM	5.1GPM / 19.3LPM	6.8GPM / 25.7LPM
Pore size	0.45 um	0.45 um	0.45 um	0.45 um
FFC Filter Capacity	10,000G / 37,500L	20,000G / 75,700L	30,000G / 113,550L	40,000G / 151,400L
Pre-coarse filter	20" 1um PP	20" 1um PP	20" 1um PP	20" 1um PP
Working pressure	15 - 60 psi	15 - 60 psi	15 - 60 psi	15 - 60 psi
Working temperature	5-38 °C	5-38 °C	5-38 °C	5-38 °C
Inlet/outlet size	3/4"	3/4"	3/4"	3/4"
Product dimensions	L355*W145*H665 mm	L452*W145*H665 mm	L549*W145*H665 mm	L646*W145*H665 mm
MOH certification	✓	✓	✓	✓
NSF Standard	NSF42	NSF42	NSF42	NSF42
Remove sediment and rust	✓	✓	✓	✓
Remove particulates	✓	✓	✓	✓
Remove residual chlorine	✓	✓	✓	✓
Remove taste & odor	✓	✓	✓	✓
Remove organic compound	✓	✓	✓	✓
Remove turbidity	✓	✓	✓	✓
Antibacterial	✓	✓	✓	✓